



ARTISAN®

Grease & Oil Emulsifier

DESCRIPTION

Artisan Grease & Oil Emulsifier is a dilutable, heavy duty product. It is a biodegradable and does not contain any bleach, caustic or phosphates. Artisan contains readily biodegradable surfactant, is effective over a wide dilution range and works equally well in hot or cold water.

USES

Use without harm to concrete, precast, manufactured stone, natural stone, brick (glazed and unglazed), masonry, clay tile, pavers, painted surfaces and any surface that is not affected or damaged by water itself.

PREPARATION

For best results and dilution ratio, test a solution and allow to thoroughly dry before general use. It will not damage glass or kill shrubs or grass.

PROPERTIES

Color	Green
Odor	Citrus
Flash Point	N/A
pH	10 - 10.5
lbs/gallon	8.4 - 8.5

APPLICATION

After determining solution strength, apply Artisan liberally onto a dry surface. Let solution stand for approximately 10-20 minutes, depending on surface and contaminates. Agitate surface using a stiff brush and rinse thoroughly. Reapply if necessary. For deep seated oil and grease stains, use Artisan Grease & Oil Remover.

PACKAGED

Available in gallons, 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

The shelf life is indefinite in closed containers. Protect from freezing.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.





SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Poly Haze Remover causes burns to the eyes. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin.

Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

STORAGE AND SHELF LIFE

Store in original closed containers. Heat reduces the shelf life. Store in a cool, dry place. Store away from alkaline products and oxidizers.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, nor can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

