



ARTISAN®

Heavy Duty Restoration Gel

DESCRIPTION

Artisan Heavy Duty Gel is a slightly acidic, light duty cleaner/restorer for use on unpolished masonry surfaces. It will remove a variety of contaminants from natural stone surfaces. Artisan H.D. Gel does not contain any bleach, abrasives, caustic, muriatic acid or petroleum distillates. It is formulated as a ready to use product.

USES

Artisan H.D. Gel can be used to clean and restore stone, brick, pavers, masonry, unglazed ceramic, travertine, marble (unpolished or unglazed), flamed granite, limestone, stucco, terrazzo, terra-cotta and other similar type surfaces; removing stains, rust, chalking, efflorescence, atmospheric stains and dirt without etching, pitting or damaging the surface or grout. Do not apply Artisan H.D. Gel on any polished surfaces. Keep away from glass and metal.

PREPARATION

For best results, test a solution of Artisan H.D. Gel before general use. It *will* damage and/or discolor glass, aluminum, polished and painted surfaces and colored grout. Keep away from plants and vegetation.

PROPERTIES

Appearance	Translucent gel
Odor	Mild
Flash Point	None
pH	5.0 - 5.5
lbs/gallon	8.5

APPLICATION

Use Artisan HD Gel full strength, do not dilute. Apply solution onto a dry surface, from the bottom up. Let solution stand for approximately 10-20 minutes, depending on surface and contaminants, agitate and rinse thoroughly.

For heavy carbon removal, use Artisan Heavy Duty Restoration Cleaner.

COVERAGE

Minimum: 100 square feet/gallon
Maximum: 150 square feet/gallon

Coverage will vary depending upon porosity and application method.

PACKAGED

Artisan HD Gel is available in gallons (4/case), 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

The shelf life for Artisan H.D. Gel is approximately 24 months in closed containers. Heat reduces the shelf life. Store in a cool, dry place.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.





Product Information

SAFETY AND HANDLING

DANGER: Corrosive Liquid. **KEEP OUT OF REACH OF CHILDREN.** For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush with water for 15 minutes, while lifting upper and lower lids. Get immediate medical attention. In case of contact with skin, wash with soap and water. If irritation develops, seek immediate medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

