



ARTISAN®

Light Duty Rust Remover

DESCRIPTION

Artisan Light Duty Rust Remover is an acidic cleaner used for the removal of surface rust from concrete, pavers, stucco, block, wood and other similar surfaces. Artisan can also be used on manufactured stone surfaces. Artisan does not contain any bleach, abrasives, phosphoric, hydrofluoric or muriatic acid.

USES

Use Artisan on stone, brick, masonry, concrete, travertine, flamed granite, limestone, stucco, terra-cotta and other similar type surfaces. Artisan removes surface rust, chalking, light efflorescence, light atmospheric stains and dirt without etching, pitting or damaging the surface or grout.

PREPARATION

It is imperative that a test be done prior to general use. Protect glass, polished surfaces, metal, painted surfaces and all other surfaces this product is not intended. Allow test areas to thoroughly dry to determine compatibility. Keep away from plants and vegetation.

EQUIPMENT

Apply using acid resistant brushes. Only apply with equipment made of polyethylene or polypropylene. Do not mix or use with any containers, tanks or applicators that are metal construction.

APPLICATION

Use Artisan full strength. Do not dilute. Apply solution onto a dry surface, from the bottom up. Let solution stand for approximately 10-20 minutes, depending on surface and contaminates. Do not allow Artisan to dry prior to rinsing. If product dries prior to rinsing, mist surface with water or reapply remover. Agitate and rinse thoroughly. NOTE: Some deep seated rust stains might require our Heavy Duty Rust Remover or a poultice.

PACKAGED

Artisan is available in gallons (4/case), 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

Close container after each use. Store in a cool, dry place. The shelf life is indefinite in closed containers. Read MSDS before using. Store away from alkalies and oxidizers.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

PROPERTIES

Appearance	Clear to yellow liquid
Odor	Mild
Flash Point	N/A
lbs/gallon	8.7 – 8.8





Product Information

SAFETY AND HANDLING

DANGER: Corrosive Liquid. **KEEP OUT OF REACH OF CHILDREN.** For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush with water for 15 minutes, while lifting upper and lower lids. Get immediate medical attention. In case of contact with skin, wash with soap and water. If irritation develops, seek immediate medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

