



ARTISAN®

Nano-Acrylic Topical Sealer

DESCRIPTION

Artisan Nano-Acrylic Topical Sealer is a stain resistant, single component, water based, safety sealer for interior or exterior applications. Because of its nano-particle size, Artisan Nano-Acrylic Topical Sealer provides an exceptionally durable coating. When dry, it is slip resistant, has excellent adhesive and cohesive properties and high abrasion and chemical resistance. It is unaffected by ultra-violet light and staining. Artisan Nano-Acrylic Topical Sealer is a high-solids, penetrating sealer that dries crystal clear and will not yellow with age.

USES

Artisan Nano-Acrylic Topical Sealer is designed for new or cleaned concrete pavers, stucco, precast, terrazzo, resilient tile, marble, granite, quarry tile, ceramic tile, flagstone, slate and other similar surfaces. Artisan can be used as a stand-alone sealer or as a base coat. NOTE: Not for use on polished or honed surfaces.

COVERAGE & PREPARATION

Two coats are recommended on most surfaces. Coverage rates vary but average 300 square feet per gallon for the first coat and 400 square feet per gallon for the second coat. All surfaces should be thoroughly cleaned prior to application to remove dirt, grease, stains and other contaminants using appropriate Artisan product. It is imperative that cleaned surfaces are thoroughly rinsed and free of cleaner residue. Cleaner residue may adversely affect the application and proper drying and curing.

PROPERTIES

Appearance	Milky/white liquid
Odor	Slight ammonia
Flash Point	N/A
lbs/gallon	8.5 - 8.8
Solids	16%

APPLICATION

Artisan Nano-Acrylic Topical Sealer can be applied by airless sprayer, low pressure sprayer, roller, brush or lambs wool applicator. Before application, surface must be clean and thoroughly dry.

When finished, immediately purge spray equipment with a solution Artisan Grease & Oil Emulsifier. Brushes and roller sleeves cannot be reused.

PACKAGED

Available in gallons (4/case), 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

Store in a cool dry room. Protect from freezing. The shelf life is 4 years in original, closed containers.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Refer to product label and material safety data sheet for complete safety information. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.





Product Information

FIRST AID: In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

SAFETY

CAUTION: Refer to the first aid information for each ingredient prior to use. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application. Avoid contact with eyes and contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Prevent mist or fumes from entering ventilation systems of occupied buildings. Close container after each use. Wash thoroughly after handling.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, nor can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

