



# ARTISAN®

## Sacrificial Anti-Graffiti Coating

### DESCRIPTION AND USES

Artisan Sacrificial Graffiti Coating is a V.O.C. compliant, water based product that provides temporary protection to painted surfaces, masonry and metal surfaces. This product develops a clear film that will not darken the surface. Artisan is U.V. stable and will not yellow. When applied onto metal surfaces, it is impervious to all naturally occurring corrosive materials. Artisan can be easily removed using our Architectural Cleaner.

### PREPARATION

Before application, protect all surfaces from unwanted overspray, wind drift, splashing and residue. Surfaces must be clean and dry before application. If necessary, prepare surface by using the appropriate Chemique cleaner. Surfaces being cleaned before application of must be free of any chemical residue. Any residue remaining on the surface will affect coating.

### APPLICATION

Before general application, always test an area typical of surface to be coated. Allow drying to determine compatibility and desired results.

- 1) Apply coating evenly, with an overlapping pattern, using brush, roller or sprayer. Do not allow to puddle or run down surface.
- 2) Allow coating to penetrate surface for several minutes. Remove excess using a brush or roller.
- 3) Porous surfaces might require a second coat. Surface will thoroughly dry within 1 hour.

After coating has dried, it is important to inspect the surface to ensure that surface is thoroughly coated—particularly on porous surfaces such as block. If the surface has an inconsistent appearance, an additional coat may be necessary.

### MAINTENANCE

The use of harsh chemicals and/or high pressure water on a treated surface will damage or remove the coating.

### GRAFFITI REMOVAL

Remove graffiti using high pressure (1000-1500 p.s.i.), hot water and Architectural Cleaner. This will remove the coating along with the unwanted graffiti. After complete removal and surface drying, reapply coating to surface for graffiti protection.

### CLEAN UP

Clean tools and equipment immediately using soap and water.

### DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

### COVERAGE RATES

Brick	150-200 sq. ft.
Concrete	150-300 sq. ft.
Painted Surfaces	300-500 sq. ft.
Block	75-100 sq. ft.
Metal	400-600 sq. ft.

### PROPERTIES

Color	Tan to milky liquid
Odor	Mild
Flash Point	None
lbs/gallon	8.3 - 8.4
V.O.C.	15 g/L





## Product Information

### PACKAGED

Available in 5 gallon pails and 55 gallon drums.

### STORAGE AND HANDLING

Store this product in a cool, dry place. Keep from freezing. Dispose of empty containers accordingly. If spilled, absorb with inert material and dispose of in accordance with local, state and federal regulations.

### PACKAGED

Available in gallons (4/case), 5 gallon pails and 55 gallon drums.

### STORAGE AND SHELF LIFE

Store in a dry room in closed containers. The shelf life is 24 months in original, closed containers. Do not allow product to freeze. Do not store above 110 degrees F for extended periods.

### SAFETY

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL:** Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

### WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

