



DWR®

Deck & Wood Coating Rejuvenator

DESCRIPTION

DWR Coating Rejuvenator is a concentrated product for cleaning, restoring and brightening exterior, natural wood decks and siding. Coating Rejuvenator can also be used for heavy duty jobs such as concrete etching and rust removal from driveways and stucco. Other uses include: paint prep cleaner, mill glaze removal and cleaning vinyl and aluminum siding. This product does not contain any bleach, chlorinated solvents or caustic.

USES

Use Coating Rejuvenator in place of ineffective bleach products or hazardous solvent based compounds. It is a proven cleaner/restorer for greying and discolored wood, mill glaze removal, concrete etching and vinyl and aluminum siding.

PREPARATION & APPLICATION

Coating Rejuvenator can be applied by brush, roller or pump-style sprayer. Prior to application, remove all furniture and children's toys from the area. Thoroughly wet down plants and vegetation before and after application to avoid damage. Do not apply to hot surfaces or in direct sunlight. Apply to a cool, dry surface. Apply Coating Rejuvenator liberally to the surface with recommended applicator. On vertical surfaces, start from the bottom. Agitate surface and rinse or power wash. If cleaner dries, mist with water or re-apply cleaner. Re-apply if necessary to achieve desired results.

TEST AREA:

Before general use, it is imperative that a small test be done, typical of the surface to be cleaned to determine compatibility.

PROPERTIES

Coverage	200-900 sq. ft./gal.
Appearance	Green liquid
Odor	Mild
Flash Point	None
lb./gallon	8.5 – 8.6

PACKAGED

Coating Rejuvenator is available in gallons (4/case), 5 gallon pails and 55 gallon drum.

SAFETY AND HANDLING

For specific information, please refer to the label and material safety data sheet. Coating Rejuvenator is corrosive to skin, eyes and mucous membranes. Wear rubber or latex gloves and eye/face protection.

STORAGE AND SHELF LIFE

Store in a cool, dry place. Keep away from acids. Shelf life is indefinite in closed containers. Refer to MSDS for additional information.

CLEAN UP

Clean tools and equipment immediately using soap and water.





Product Information

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY

DANGER: Corrosive liquid. Contains phosphoric acid. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application. Avoid contact with eyes and contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Prevent mist or fumes from entering ventilation systems of occupied buildings. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, immediately flush with water for 15 minutes, while lifting upper and lower lids. Get immediate medical attention. **SKIN:** Immediately wash affected area with soap and water until all traces of chemical residue are gone. Get medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDRE.** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

