



DWR®

Deck & Wood Stripper

DESCRIPTION

DWR Stripper is a viscous, red liquid for the removal of oil based stains, clear finishes, water based stains and latex. DWR Stripper is a biodegradable, environmentally safe product that provides excellent results economically. Does not contain any bleach, chlorinated solvents or acids.

USES

Use Stripper in place of ineffective bleach products or hazardous solvent based compounds. It is a proven remover for stains, finishes and discolorations that are caused by sunlight, moisture, mold, mildew and ground in dirt and grease on natural wood surfaces.

PREPARATION & APPLICATION

DWR Stripper is a ready to use product that can be applied by brush, roller or pump-style sprayer. Prior to application, remove all furniture, metal fixtures and children's toys from the area. Thoroughly wet down plants and vegetation before and after application to avoid damage. Do not apply to hot surfaces or in direct sunlight. Apply to a cool, dry surface. Apply stripper liberally to the surface with recommended applicator. On vertical surfaces, start from the bottom and work up. Wait 5 to 10 minutes or until coating has softened or lifted. Do not allow stripper to dry. If it dries, spray with water or re-apply stripper. Agitate surface with a stiff brush and thoroughly rinse or power wash to remove coating.

Use DWR Brightener & Neutralizer, to neutralize any remaining stripper and brighten wood darkened by stripper or through age. Wait until surface is thoroughly dry before applying stain or any other coating. Lightly sanding surface will help coating penetration and adhesion.

PROPERTIES

| | |
|-------------|----------------------|
| Coverage | 125-150 sq. ft./gal. |
| Appearance | Viscous, red liquid |
| Odor | Mild |
| Flash Point | None |
| pH | 14 |

PACKAGED

DWR Stripper is available in gallons (4/case), 5 gallon pails and a professional strength concentrate.

SAFETY AND HANDLING

For specific information, please refer to the label and material safety data sheet. Stripper is corrosive to skin, eyes and mucous membranes. Wear rubber or other impervious gloves and eye/face protection.

STORAGE AND SHELF LIFE

Store in a cool, dry place. Keep away from acids. Shelf life is indefinite in closed containers. Refer to MSDS for additional information. Protect from freezing.

CLEAN UP

Clean tools and equipment immediately using soap and water.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.





Product Information

SAFETY

DANGER: Corrosive liquid. Contains sodium hydroxide and sodium metasilicate. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application. Avoid contact with eyes and contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Prevent mist or fumes from entering ventilation systems of occupied buildings. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, immediately flush with water for 15 minutes, while lifting upper and lower lids. Get immediate medical attention. **SKIN:** Immediately wash affected area with soap and water until all traces of chemical residue are gone. Get medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly.

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

