



# Product Information

## ARTISAN® Penetrating Enhancer & Repellent

### DESCRIPTION

Artisan Penetrating Enhancer & Repellent is a high solids, water based product for interior and exterior applications. Artisan provides a breathable, color enhanced finish that inhibits water and stain cause materials from penetrating the surface.

### USES

Apply Artisan to new or cleaned pavers, architectural concrete block, brick, slate, flamed granite, tumbled marble, non-polished/non-honed limestone, flagstone, stucco, sandstone and other masonry surfaces. Effective on horizontal and vertical surfaces. Do not apply to any polished or honed surfaces.

### PREPARATION

Two coats may be necessary on porous surfaces. Only one application may be necessary for smooth, dense surfaces. Surface must be clean and dry prior to application.

### COVERAGE PER GALLON

Architectural Concrete Block	50-100 sq ft.
Brick	100-150 sq ft.
Pavers	100-150 sq ft.
Flagstone	150-200 sq ft.
Slate	150-200 sq ft.
Flamed Granite	200-250 sq ft.
Tumbled Marble	100-175 sq ft.

### PROPERTIES

Appearance	Milky liquid
Odor	Mild
Flash Point	N/A
lbs/gallon	8.4

### APPLICATION

Apply by spray, roller, brush or lambs wool applicator. Before applying, surface must be clean and free of any residue from cleaners. Do not apply on hot surfaces. Do not flood surface. Over application will inhibit proper drying. Refer to Coverage chart for approximate rates.

### DRY AND CURE

Product will be dry to the touch within 20-30 minutes at temperatures of 50-85 degrees F. Colder temperatures and high humidity will extend dry times. Under ambient temperatures, product will cure in 24 hours.

### CLEAN UP

Clean tools and equipment immediately using soap and water.

### DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

### PACKAGED

Available in gallons (4/case), 5 gallon pails and 55 gallon drums.

### STORAGE AND SHELF LIFE

Keep from freezing. Store in a cool, dry room. The shelf life is 12 months in closed containers at room temperature. Do not store above 90 degrees F or in direct sunlight.





## Product Information

### ARTISAN® Penetrating Enhancer & Repellent

#### SAFETY

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Prevent mist or fumes from entering ventilation systems of occupied buildings. Close container after each use. Wash thoroughly after handling.

**FIRST AID:** In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL:** Absorb with inert material and dispose of properly.

**KEEP OUT OF REACH OF CHILDREN**

Refer to Material Safety Data Sheet available for further safety and handling information.

#### WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc.'s liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

