



## Product Information

### DWR-II®

#### Graffiti Remover

#### DESCRIPTION

DWR-II is a zero V.O.C. graffiti remover for use on surfaces treated with an anti graffiti treatment or barrier coating and painted surfaces. It is a water rinseable remover. DWR-II will dissolve, suspend and remove deeply imbedded markings, defacements and adhesive from a variety of surfaces.

DWR-II does not contain any chlorinated solvents, aromatic solvents, caustics or acids.

#### USES

DWR-II can be used on stone, brick, block, manufactured stone, general masonry, ceramic, porcelain, fiberglass, non-anodized metal, stainless, glass, plastics, marble, wood and painted surfaces for the removal of graffiti. DWR-II works best on smooth surfaces and those treated with one of our anti graffiti protectants.

#### PREPARATION

Test to determine compatibility and dwell time before general use. For best results, test a solution on an inconspicuous area and allow to dry before general use. Protect all other surfaces that this product is not intended for use.

#### PROPERTIES

Appearance	Clear/viscous liquid
Odor	Slight solvent
Flash Point	>200 degrees F (c.c.)
V.O.C.	0
lbs/gallon	8.0 - 8.2

#### APPLICATION

Do not dilute DWR-II. Apply onto a dry surface, using a brush, roller or sprayer. Let stand for five minutes. Lightly agitate surface and rinse thoroughly. Some surfaces may require a second application. If applying an anti graffiti treatment, wait until surface is completely dry and free of any remover residue.

#### PACKAGED

DWR-II is available in pints (12/case), gallons (6/case), 5 gallon pails and 55 gallon drums.

#### STORAGE AND SHELF LIFE

Store in a cool, dry room. Keep away from heat, sparks and flame. The shelf life for DWR-II is indefinite in closed containers. Read MSDS before use.

#### DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

#### STORAGE AND SHELF LIFE

Store in a cool dry room in original, closed containers. Keep away from acid and alkaline products.

#### TRANSPORTATION

Not regulated by the U.S. Department of Transportation for ground shipments.





## Product Information

### DWR-II®

Graffiti Remover

#### SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL:** Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

#### WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.



ARTISAN®  
STONE CARE PRODUCTS

ION®

