Product Information



STRIPIT 25®

Heavy Duty Remover

DESCRIPTION & USES

Stripit 25 is a biodegradable, V.O.C. compliant, heavy duty, water rinseable remover for interior or exterior use. Stripit 25 does not contain any chlorinated solvents, caustics or acids. A unique combination of surfactants and special solvents, Stripit 25 will safely and effectively remove urethanes, epoxies, lacquers, acrylic curing compounds, enamels, graffiti, floor finish build-up, adhesive, latex paint, acrylic and other sealers.

StripIt 25 can be safely used on concrete, brick, pavers, natural stone, metal, wood, ceramic and other surfaces.

Do not use on asphalt, rubber, painted surfaces, resilent tile and other surfaces this product is not intended for.

PREPARATION

Test to determine compatibility and dwell time before general use. Work in small, manageable areas, rinse and allow to dry before general application. Protect surrounding surfaces, plants and vegetation.

APPLICATION

Do not dilute Stripit 25. Apply liberally to a dry surface with a brush, roller or sprayer. Allow sufficient time to penetrate the surface. Depending on type of coating being removed and number of coats, dwell times can vary from 30 minutes to several hours. Once StripIt has started lifting the coating, scrape and or power wash to remove. A second application may be necessary or longer dwell time.

PROPERTIES

Appearance Clear-amber, viscous liquid
Odor Mild solvent
Flash Point 202°F (c.c.)
pH 7.0 – 7.4
lbs/gallon 7.3

COVERAGE

Coverage varies depending upon the type of product being removed and application method, but is generally between 75-100 square feet per gallon.

PACKAGED

Stripit 25 is available in gallons (4/case), 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

Close container after each use. Store in a cool, dry place. The shelf life of Stripit 25 is indefinite in closed containers. Read MSDS before using.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.













Product Information



STRIPIT 25®

Heavy Duty Remover

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. FIRST AID: EYES: Flush with water for 15 minutes, while lifting the upper and lower lids. Get medical attention. SKIN: Wash affected area with soap and water until all traces of residue are gone. Remove contaminated clothing and launder before reuse. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly.

KEEP OUT OF REACH OF CHILDREN. Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.











