



StripIt®

Safer Water Based Paint Remover

DESCRIPTION & USES

Stripit Safer Water Based Paint Remover is a non-hazardous paint and coating remover, with zero V.O.C. that can be used for interior and exterior applications. Stripit does not contain any methylene chloride, methanol, NMP, petroleum distillates or caustic. This truly unique, water based remover can be used to remove multiple coats of latex, acrylic, urethane, varnish, lacquer, floor finish build-up, adhesive, lead based paint and architectural and industrial coatings.

StripIt can be safely used on concrete, brick, pavers, natural stone, metal, wood, ceramic, fiberglass and other surfaces. StripIt does not require neutralization.

PREPARATION

Test to determine compatibility and dwell time before general use. Work in small, manageable areas, rinse and allow surface to dry before general application. Protect surrounding surfaces, plants and vegetation.

APPLICATION

Do not dilute Stripit. Apply liberally to a dry surface with a brush, trowel or airless sprayer. Allow sufficient time to penetrate the surface. Depending on type of coating being removed and number of coats, dwell times can vary from 30 minutes to 48 hours. Once StripIt has lifted the paint from the surface, scrape off residue and dispose according to local, state and federal regulations. Rinse any remaining residue with clean water. A second application may be necessary or longer dwell time.

CLEAN UP

Clean all applicators and equipment with soap and water or denatured alcohol. Do not store or collect remover and/or paint residue in metal containers. Use plastic containers only.

WARNING! Lead dust may be released if you sand, scrape or mechanically remove old paint. Lead is toxic. Exposure to lead dust can cause serious illness such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before starting a project, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. NOTE: StripIt is designed to keep lead paint wet, which will prevent toxic lead dust from becoming airborne.

PROPERTIES

Appearance	White, viscous
Odor	Mild, sweet
Flash Point	>204°F (benzyl)
pH	10
lbs/gallon	9.1

COVERAGE

Coverage varies depending upon the type of product being removed and application method, but is generally between 40-55 square feet per gallon.

PACKAGED

Stripit is available in 5 gallon pails and 55 gallon drums.





Product Information

STORAGE AND SHELF LIFE

Close container after each use. Keep away from open flame and heat sources. Protect from freezing. The shelf life is indefinite in original, closed containers at ambient temperatures.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

TRANSPORTATION

Not regulated by the U.S. Department of Transportation for ground shipments.

SAFETY AND HANDLING

StripIt will de-fat skin, wear butyl rubber gloves, goggles, protective apron and footwear. When spraying or working in confined areas, wear appropriate cartridge respirator for ingredients listed on material safety data sheet. For specific information, please refer to the material safety data sheet, label and the product information sheet. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. Close container after each use. **FIRST AID: EYES:** Immediately flush with water for 15 minutes, while lifting the upper and lower lids. Seek immediate medical attention. **SKIN:** Immediately wash with soap and water until all traces of residue are gone. Remove contaminated clothing and launder before reuse.

SWALLOWED: If swallowed, rinse mouth out with water and give 1 glass of water. Do not induce vomiting. Contact poison control center, physician or hospital for instructions. **INHALATION:** If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. **IN CASE OF SPILL:** Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose. Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

