



ARTISAN®

2-Part Anti-Graffiti Barrier Coating

DESCRIPTION AND USES

Artisan is a permanent, two component, non-sacrificial, fluorinated, waterborne coating for superior protection against graffiti, harsh chemicals and severe environmental exposure. Artisan contains a fluorinated resin which inhibits graffiti penetration for quick and easy graffiti removal. Artisan can be applied to a wide variety of substrates including brick, concrete, stucco, manufactured stone, wood, painted surfaces, metal and plastic. Artisan is suitable for both interior and exterior applications. Artisan is available in clear and a tintable, white formula.

TEST AREA AND PREPARATION

Test patch before general use to determine compatibility, yield and desired results. All surfaces must be thoroughly cleaned and rinsed with appropriate Chemique product. Surfaces must be free of any chemical residue and dry before application. Chemical residue and moisture will adversely affect coating properties. Metal and plastic surfaces should be lightly sanded and primed. Before application, protect all surfaces from unwanted overspray, wind drift, splashing and residue.

PHYSICAL DATA

Appearance (part A)	Clear or pigmented
(part B)	Clear/pale yellow
Solids by volume:	44%
VOC:	98 g/L
Pot Life:	5 hours
Dry Time:	1-2 hours
Recoat Time:	2-3 hours
Cure Time:	7-10 days

APPLICATION

Add one container part B to one container part A and mix thoroughly. Pot life is approximately 5 hours at ambient temperatures. Coating may be applied by spray, brush or roller. As a graffiti barrier, a minimum of two coats is recommended. Recoat time is 2-3 hours depending on temperature and humidity.

Dry film thickness is 2 mils/coat when applied at a rate of 300-400 square feet/gallon on painted surfaces. Average drying time is 1-2 hours. Maximum hardness is realized in 7-10 days depending on temperature.

COLOR TINTING

To tint, add water based color dispersion to tintable, white Part A. NOTE: Adding colorant can affect dry and cure times as well as graffiti removal properties.

PACKAGED

Artisan is available in one gallon and five gallon kits.

STORAGE AND SHELF LIFE

Keep mixed solutions and "B" component away from heat sources, sparks and flames. Part "B" is flammable. The shelf life is 6 months in closed containers. Opening and closing containers, reduces the shelf life. Protect Part A from freezing. The shelf life of Part A is 18 months in original, closed containers.





Product Information

ORDERING INFORMATION

Please call us for your local distributor.
Chemique, Inc.
315 N. Washington Ave.
Moorestown, NJ 08057
TEL: 856-235-4161

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY

Part "B" is flammable. Use with adequate ventilation. Wear gloves, goggles and respirator with cartridges suitable for this product. For specific information, please refer to the material safety data sheet. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Prevent mist or fumes from entering ventilation systems of occupied buildings. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly.

KEEP OUT OF REACH OF CHILDREN

Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

