

StripIt[®]

Pro Strength Neutralizer

DESCRIPTION

StripIt[®] Professional Neutralizer is a concentrated, liquid neutralizing agent that must be used after using our StripIt[®] Heavy Duty Alkaline Paint Remover or StripIt[®] Extra Heavy Duty Paint Remover. It is imperative that StripIt[®] Professional Neutralizer is used to reduce surface pH, even if the surface is not being painted after removal.

USES

Use StripIt[®] Professional Neutralizer on interior and exterior surfaces including concrete, brick, stone, metal, wood, fiberglass and other similar surfaces. Wood surfaces will darken after using StripIt[®] Heavy Duty Alkaline Paint Remover or StripIt[®] Extra Heavy Duty Paint Remover. Applying this product will restore the original color of the wood as well as neutralizing the caustic residue.

PREPARATION

For best results, test a solution following the directions on the container, then test pH before general use.

APPLICATION

Mix 1 part StripIt Pro Strength Neutralizer with 1 part clean water. Add the Neutralizer to the clean water, in a plastic pail. DO NOT add the Neutralizer to water. DO NOT mix in anything other than a plastic container. Apply solution liberally onto the surface. Let solution stand for approximately 10-20 minutes. Agitate surface using a stiff brush and rinse thoroughly. Check pH, which should be between 5-8. If pH remains high, leave neutralizer on the surface until it dries. Rinse with clean water and check pH again.

PROPERTIES

Appearance	Clear/turbid liquid
Odor	Pungent
Flash Point	N/A

PACKAGED

Available in 5 gallon pails.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. StripIt Professional Strength Neutralizer is corrosive and causes eye and skin burns. May cause respiratory irritation. Wear chemical resistant gloves, apron, footwear face shield and goggles. Refer to product label and safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. Get immediate medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

SAFETY AND HANDLING

IN CASE OF SPILL: Absorb with inert material and dispose of properly. KEEP OUT OF REACH OF CHILDREN. Refer to Safety Data Sheet available for further safety and handling information.

STORAGE AND SHELF LIFE

Store in a cool, dry place. Store away from incompatible materials. Shelf life is 36-48 months in original, closed containers.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, nor can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc.'s liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

