



StripIt®

Safer Solvent Based Remover

DESCRIPTION & USES

Stripit is a biodegradable, V.O.C. compliant, heavy duty, water rinseable remover for interior or exterior use. Stripit does not contain any chlorinated solvents, caustics or acids. Stripit will safely and effectively remove urethanes, epoxies, lacquers, acrylic curing compounds, enamels, graffiti, floor finish build-up, adhesive, latex paint, acrylic and other sealers.

StripIt can be safely used on concrete, brick, pavers, natural stone, metal, wood, ceramic and other surfaces. NOTE: Do not use on asphalt, rubber, resilient tile and other surfaces this product is not intended.

PREPARATION

Test to determine compatibility and dwell time before general use. Work in small, manageable areas, rinse and allow to dry before general application. Protect surrounding surfaces, plants and vegetation.

APPLICATION

Do not dilute Stripit. Apply liberally to a dry surface with a brush, roller, trowel or sprayer. Allow sufficient time to penetrate the surface. Depending on type of coating being removed and number of coats, dwell times can vary from 30 minutes to several days. Once StripIt has started lifting the coating, scrape to remove from surface. Wash remaining residue with water. A second application may be necessary or longer dwell time.

CLEAN UP

Clean all applicators and equipment with soap and water or denatured alcohol. Do not store or collect remover and/or paint residue in metal containers. Use plastic containers only.

WARNING! Lead dust may be released if you sand, scrape or remove old paint. Lead is toxic. Exposure to lead dust can cause serious illness such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before starting a project, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PROPERTIES

Appearance	Opaque paste
Odor	Mild solvent
Flash Point	>200°F
pH	3.5
lbs/gallon	9.6

COVERAGE

Coverage varies depending upon the type of product being removed and application method, but is generally between 40-60 square feet per gallon.

PACKAGED

Stripit is available in 5 gallon pails and 55 gallon drums.





Product Information

STORAGE AND SHELF LIFE

Close container after each use. Store in a cool, dry place and away from open flame and heat sources. The shelf life of Stripit is indefinite in closed containers. Read MSDS before using.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mists by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** EYES: Flush with water for 15 minutes, while lifting the upper and lower lids. Get immediate medical attention. SKIN: Wash affected area with soap and water until all traces of residue are gone. If irritation develops seek medical attention. Remove contaminated clothing and launder before reuse. SWALLOWED: Rinse mouth out immediately with water and give 1 glass of water. DO NOT induce vomiting. Immediately call a poison control center, physician or hospital emergency room for instructions.

INHALATION: If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. **IN CASE OF SPILL:** Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc.'s liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

