

ARTISAN[®]

Safer Light Duty Restoration Cleaner

DESCRIPTION

Artisan Safer Light Duty Restoration Cleaner is an exceptionally effective combination of acids, surfactants and inhibitors, as a gelled solution. The gelled consistency allows the applicator to easily control the cleaner. This product does not contain any harsh hydrochloric or hydrofluoric, which can etch and increase surface porosity.

This cleaner is safer and less corrosive than restoration cleaners that contain hydrofluoric acid or ammonium bifluoride. It is non-fuming and has a very low odor.

USES

Use Artisan Safer Light Duty Restoration Cleaner to remove atmospheric staining, discolorations and general dirt from many masonry surfaces. Use Artisan on concrete, architectural concrete block, brick, honed and polished granite, unpolished marble/travertine/limestone, sandstone, terra cotta, slate and other similar surfaces.

PREPARATION

For best results, test a solution of Artisan before general use. Protect metal and glass. Keep away from plants and vegetation.

PROPERTIES

Appearance	Slightly turbid gel
Odor	Mild
pH	2.0 - 2.5
lbs/gallon	8.6

SURFACE & AIR TEMPERATURES

Do not apply onto a hot surface. Do not apply in freezing temperatures, or if temperatures are expected to fall below freezing overnight.

APPLICATION

Use Artisan Safer Light Duty Restoration Cleaner full strength. Do not dilute. Use acid resistant brushes and roller. Apply solution onto a dry surface, starting from the bottom and working up. Let solution stand for approximately 15-30 minutes, depending on surface and contaminates. Gently scrub surface and rinse thoroughly.

COVERAGE

Minimum: 75-125 square feet/gallon on porous surfaces.

Maximum: 150-200 square feet/gallon on smooth, dense surfaces.

Coverage rates will vary depending upon porosity and application method.

PACKAGED

Artisan Safer Heavy Duty Restoration Cleaner is available in gallons (4/case), 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

The shelf life for Artisan Safer Light Duty Restoration Gel is approximately 24 months in closed containers. Heat reduces the shelf life. Store product in a cool, dry place.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

CLEAN UP

Clean rollers and brushes using soap and water.

SAFETY AND HANDLING

DANGER: Corrosive Liquid. KEEP OUT OF REACH OF CHILDREN. For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

FIRST AID: In case of eye contact, flush with water for 15 minutes, while lifting upper and lower lids. Get immediate medical attention. In case of contact with skin, wash with soap and water. If irritation develops, seek immediate medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. KEEP OUT OF REACH OF CHILDREN. Refer to Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc.'s liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

