

# StripIt<sup>®</sup> SPRAY

Paint Remover for Small Jobs

## DESCRIPTION & USES

StripIt SPRAY Paint Remover is BOTH eco-friendly & convenient. Consumers have often been left with the unwelcome choice of using a messy remover that is hard to apply, especially on vertical surfaces. Many also contain harsh chemicals that are flammable or had limitations. Now, that has all changed. With StripIt SPRAY, you have a remover that is easy to apply with a trigger sprayer, doesn't drip and is perfect for small jobs.

StripIt SPRAY is a water based remover that does not contain any hazardous methylene chloride, NMP, methanol, acetone, petroleum distillates or caustic. StripIt is non-flammable, non-combustible and practically odor free. StripIt can be safely used on interior and exterior surfaces including wood, concrete, brick, plaster, stone, metal, fiberglass and many other surfaces. StripIt is excellent for horizontal and vertical surfaces. StripIt will remove most varieties of paint including oil and water based paints, varnishes, latex, stains, acrylics, enamels, lacquers and polyurethanes. DO NOT use on sheetrock or linoleum surfaces.

## TEST AREA

Before general use, it is imperative to test on a small, inconspicuous area to determine compatibility, required dwell time, coverage and desired results. The user shall determine the suitability of the product for its intended use(s), and user assumes all risk and liability whatsoever in connection therewith.

## HOW TO USE

1. Shake well before using. Cover/protect/mask areas with plastic sheeting where removal is not required. Cover plants & vegetation. Rubber gloves & safety glasses are recommended for eye & skin protection. 2. StripIt is ready to use. Do not dilute. 3. Apply as heavily as possible on vertical surfaces and liberally on horizontal surfaces so that the stripper completely masks the color of the surface. For best results, apply between 60F - 80F. Lower temperatures will increase dwell time and higher temps will dry out remover. 4. Check applied area at 30 minutes to 4 hours, and periodically thereafter. StripIt stays active for up to 12 hours for tougher coatings.

5. Once paint/coating has softened, use a paint stripping tool to lift paint from flat surfaces or a stiff bristle brush for detailed areas. 6. If you are not down to the original surface, as long as StripIt is still wet, leave the stripper on longer and then remove. You can also mist the applied area with water or StripIt Final Wash, wait 5-15 minutes and remove. 7. After removal, use a scrub pad or nylon brush with StripIt Final Wash or a light amount of water for final clean-up of residue. Re-apply if necessary. 8. Let surface dry before refinishing. No need to neutralize (acid wash) surface.

## CLEAN UP

Clean all applicators and equipment with soap and water. Do not store or collect remover and/or paint residue in metal containers. Use plastic containers only.

WARNING! Lead dust may be released if you sand, scrape or mechanically remove old paint. Lead is toxic. Exposure to lead dust can cause serious illness such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before starting a project, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). NOTE: StripIt is designed to keep lead paint wet, which will prevent toxic lead dust from becoming airborne.

## PROPERTIES

Appearance	White gel
Odor	Mild, sweet
Flash Point	>204°F (benzyl)
pH	10.5
lbs/gallon	8.5

## COVERAGE

Coverage varies depending upon the type of coating being removed & application method, but is approximately 100 square feet per gallon,



### PACKAGED

StripIt SPRAY Paint Remover is available in 22 ounce spray bottles.

### STORAGE AND SHELF LIFE

Close container after each use. Keep away from open flame and heat sources. Protect from freezing. The shelf life is 3 years in original, closed containers at ambient temperatures.

### DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

### SAFETY AND HANDLING

StripIt SPRAY will de-fat skin, wear butyl rubber gloves, goggles, protective apron and footwear. When spraying or working in confined areas, wear appropriate cartridge respirator for ingredients listed on safety data sheet. For specific information, please refer to the safety data sheet, label and the product information sheet. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. Close container after each use.

**FIRST AID:** EYES: Immediately flush with water for at least 20 minutes, while lifting the upper and lower lids. If wearing contact lenses, remove and continue flushing with water. Seek immediate medical attention. SKIN: Wash with soap and water until all traces of residue are gone. Remove contaminated clothing and launder before reuse. SWALLOWED: If swallowed, rinse mouth out with water and give 1 glass of water if person is alert. Do not induce vomiting. Immediately contact poison control center, physician or hospital for instructions. INHALATION: If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. KEEP OUT OF REACH OF CHILDREN Refer to Safety Data Sheet available for further safety and handling information.

### WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose. Chemique warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, or its distributors.