

StripIt[®] CLEAR

Sprayable Paver Coating Remover

DESCRIPTION & USES

StripIt CLEAR Paver Coating Remover is a professional, sprayable coating remover that is BOTH eco-friendly and effective. Until now, applicators have often been left with the unwelcome choice of using a remover that is flammable, or contained harsh chemicals. Now, that has all changed. With StripIt CLEAR, you have a coating remover that has superior performance and is easy to use.

StripIt CLEAR Paver Coating Remover is a non-hazardous remover that has ultra-low V.O.C. StripIt does not contain any hazardous methylene chloride, NMP, methanol, acetone, petroleum distillates or caustic. StripIt CLEAR is non-flammable, non-combustible and practically odor free. StripIt CLEAR can be safely used on pavers, brick, concrete, natural stone, wood and other surfaces. StripIt CLEAR will remove most varieties of paver coatings including solvent and water based coatings, acrylics and polyurethanes.

TEST AREA

Before general use, it is imperative to test on a small, inconspicuous area to determine compatibility, required dwell time, coverage and desired results. The user shall determine the suitability of the product for its intended use(s), and user assumes all risk and liability whatsoever in connection therewith.

How To Use

1. Shake well before using. Cover/protect/mask areas with plastic sheeting where removal is not required. Protect surrounding surfaces, plants and vegetation. Rubber gloves & safety glasses are recommended for eye & skin protection. 2. StripIt is ready to use. Do not dilute. 3. Apply liberally onto the dry surface using a plastic tank sprayer, brush, roller or airless sprayer. Do not apply too thin. For best results, apply between 60F - 80F. 4. Allow sufficient time to penetrate the coating. Dwell time is dependent upon the type of coating being removed and the number of coats. Check applied area at 30 minutes to 4 hours, then periodically thereafter.

In some circumstances, the white StripIt will turn clear, which usually indicates the coating is ready for removal. StripIt remains wet and active up to 12 hours for tougher coatings. 5. Once coating has softened, remove coating using a pressure washer. 6. Remove any remaining residue with StripIt Final Wash or use clean water. A second application may be necessary and/or longer dwell time. 8. Let surface thoroughly dry before applying any coating. No need to neutralize (acid wash) surface.

CLEAN UP

Clean all applicators and equipment with soap and water. Do not store or collect remover and/or paint residue in metal containers. Use plastic containers only.

WARNING! Lead dust may be released if you sand, scrape or mechanically remove old paint. Lead is toxic. Exposure to lead dust can cause serious illness such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before starting a project, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. NOTE: StripIt is designed to keep lead paint wet, which will prevent toxic lead dust from becoming airborne.

PROPERTIES

Appearance	Milky liquid
Odor	Mild, sweet
Flash Point	>204°F (benzyl)
pH	10.5
lbs/gallon	8.5

COVERAGE

Coverage varies depending upon the type of coating being removed & application method, but is approximately 100 square feet per gallon.

PACKAGED

StripIt CLEAR Paver Coating Remover is available in 1 gallon, 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

Close container after each use. Keep away from open flame and heat sources. Protect from freezing. The shelf life is 3 years in original, closed containers at ambient temperatures.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.

SAFETY AND HANDLING

StripIt CLEAR will de-fat skin, wear butyl rubber gloves, goggles, protective apron and footwear. When spraying or working in confined areas, wear appropriate cartridge respirator for ingredients listed on safety data sheet. For specific information, please refer to the safety data sheet, label and the product information sheet. Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. Close container after each use.

FIRST AID: EYES: Immediately flush with water for at least 20 minutes, while lifting the upper and lower lids. If wearing contact lenses, remove and continue flushing with water. Seek immediate medical attention. SKIN: Wash with soap and water until all traces of residue are gone. Remove contaminated clothing and launder before reuse. SWALLOWED: If swallowed, rinse mouth out with water and give 1 glass of water if person is alert. Do not induce vomiting. Immediately contact poison control center, physician or hospital for instructions. INHALATION: If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. KEEP OUT OF REACH OF CHILDREN Refer to Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose. Chemique warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, or its distributors.